

Body: Double layer seimans steel filled with a 3" inner layer of tough 8000 PSI high density concrete embodied

with corundum aggregate.

Lock: Dependable U.L. Group 2 combination locks protected by a tempered glass plate. The 7-lever keylock provides additional security and daytime convenience.

Bolts: Massive 1" locking bolts.

Glass Relockers: Tempered glass plate triggers dual passive relockers in addition to a lock case relocker.

Interior: Totally adjustable shelves at 1/2" increments. Key locking drawer on intermediate models (optional on all models).

Hinges: Heavy duty, wrap around locks secured with independent fixed locking bolts.

The Advanced Protector TL-15

Mutual proudly introduces another fine product in their line of quality safes. Incorporating advanced level security defense systems, this safe is an extension of Mutual's DP series. For those seeking a certified degree of security the Advanced Protector TL-15 offers a U.L. burglary label and a S.A.B.S. Group 1 one hour fire label.

MUTUAL

MODEL AP2/15

| Н | W | D |
|----|----------|-----|
| 25 | 19% | 19% |
| | INTERIOR | |
| 19 | 12¾ | 12 |
















| DIMENSIONS, WEIGHTS AND FEATURE | FEATURES | WEIGHTS A | DIMENSIONS. |
|--|-----------------|------------------|-------------|
|--|-----------------|------------------|-------------|

| MODEL | EXTERIOR | | INTERIOR | | SHELVI | ES/ | CAPACITY | | WEIGHT | | |
|---------|----------|-------|----------|-------|--------|------|----------|--------|---------|--------|-------|
| | Н | W | D | Н | W | D | DRAWE | RS | CU. FT. | | (LBS) |
| AP1/15* | 191/2 | 173/4 | 173/4 | 131/2 | 111/2 | 11 | 1/0 | | 1.0 | | 430 |
| AP2/15E | 25 | 173/4 | REVISE | 19 | PEVIS | E 11 | 1/1 | REVISE | 1.3 | REVISE | 505 |
| AP3/15 | 311/2 | 193/4 | 19¾ | 241/4 | 12¾ | 12 | 1/1 | F | 2.1 | | 755 |
| AP4/15 | 311/2 | 271/2 | 271/2 | 251/4 | 211/2 | 20 | 1/1 | | 6.3 | | 1260 |
| AP5/15 | 391/2 | 271/2 | 271/2 | 321/2 | 201/2 | 21 | 2/1 | | 8.1 | | 1460 |
| AP6/15 | 49 | 29½ | 291/2 | 42 | 23 | 21 | 3/0 | | 11.74 | * | 2040 |
| AP7/15 | 59 | 291/2 | 291/2 | 52 | 23 | 21 | 3/0 | | 14.53 | | 2460 |
| AP8/15 | 67 | 411/2 | 28 | 60 | 341/2 | 20 | 4/0 | | 24.00 | | 3240 |

^{*}AP1 not available with keylock **Add 1 1/2" to depth for handles and hinges



Lab tested at 1760°F for one hour—S.A.B.S. Group 1.



DOOR SWING PROJECTIONS

| DOOR SWING DIMENSIONS | | | | | |
|-----------------------|--------|-------------|-------|--|--|
| MODEL | Α | В | С | | |
| AP1/15 | 111/2 | 321/4 | 301/2 | | |
| APEZISES | revise | 321/AREVISE | 301/2 | | |
| AP3/15 | 123/4 | 351/4 | 331/2 | | |
| AP4/15 | 211/2 | 51% | 49¾ | | |
| AP5/15 | 211/2 | 51% | 49¾ | | |
| AP6/15 | 23 | 531/2 | 511/2 | | |
| AP7/15 | 23 | 531/2 | 511/2 | | |
| AP8/15 | 341/2 | 651/2 | 761/2 | | |

