Internationa GemVault TRTL 30x6

Six-Sided Protection plus Fire Protection

Alloy Construction All Six Sides

The massive 8½° thick door and 5° thick body contain a solid layer of aluminum with corundum and copper inclusions behind a massive high density barrier material encorporating carbon fiber and other anti-penetration materials

Adjustable Shelves

A convenient arrangement of adjustable shelves is provided with each safe. Lockable compartments are optional.

Massive 4-way Active Boltwork

The four-way moving boltwork engages both vertically and horizontally into the protective casting of the body. The bolts are an impressive 2* in diameter.







Adjustable Ball Bearing Hinges

Fiber-Optic Protection Over Keylock

The most vulnerable point of entry for fiberoptics is through the keyhole which is protected by an antifiberoptic keyhole cover lock.


U.L. Approved Combination Lock

Locking is by Group 1 UL classified combination lock with key change capability. In addition, the safe has a high-security keylock with keys provided in triplicate.

Convenient Round Turn/ Pull Handle

MODEL GV-4720

The International GemVault TRTL-30x6 is the outcome of over 75 years of concentrated research and development by one of the world's major safe and vault manufacturers of high-security safes and vaults since 1912. The GemVault TRTL-30x6 incorporates many of the same design features found on safes costing much more. One of the most unique features that has been incorporated in this safe is the anti-fiberoptic keyhole cover lock, which prevents burgulars from inserting fiberoptic devices into the keyhole.





c <u>noa</u>]

V5920 GV6829

GV6836

International GemVault TRTL 30x6


MODEL	Interna	al Diame W	eter/in. D	Extern H	al Diam W	eter/in. D*	Capacity Cu. Ft.	Door Lbs.	Body Lbs.	Total Lbs.	No. of Shelves
GV3520	35	20	20	46	31	341/2	8.5	725	2175	2900	2
GV4720	47	20	20	58	31	341/2	11.4	975	2925	3900	3
GV5920	59	20	20	70	31	34½	14.3	1050	3150	4200	4
GV6829	68	29	18	79	40	32	20.25	1295	3885	5180	4
GV6836	68	36	26	79	47	38½	35.4	1705	5115	6820	5

^{*}Add 23/4" to depth for handle & hinges

We reserve the right to alter any specifications or make any improvements without prior notice.

Door Swing Dimensions

140051							
MODEL		Door Swings					
	Α	В	C				
GV3520	20	62	551/2				
GV4720	20	62	551/2				
GV5920	20	62	551/2				
GV6829	29	69	74	_			
GV6836	36	841/2	881/2				



Distributed By:

