

O R I G I N A L



U L T L 3 O





SAFE & VAULT INC.

SAFE DOOR

Constructed of high strength composite materials developed by Original Safe & Vault Inc. With an overall door thickness of 6.75 inches, Original has included yet another proprietary super alloy in the plate surrounding the inner door lining.

SAFE BODY

Constructed of the same high strength composite materials with an overall thickness of 3.5 inches. Original's anti-peel Zee Bar system is fastened to the inner and outer structure of the body.

BOLT WORK

Moving and fixed bolts are a full 1.5 inches in diameter. Receiver cups are welded to the super alloy inner body lining.

DUAL LOCKING
Locking by a Group 2
combination lock with over
one million combinations and
a high security key lock. The
locks are interchangeable.

Electronic locks are optional.


LOCKING MECHANISM
Lock mechanism is protected
by a random relocking system.
A tempered glass trigger will
activate the relocking system
in the event of an attack.

BASTION

Original Safe & Vault Co. reserves the right to alter any specification and make necessary improvements in the interest of providing maximum security. Shelves are removable and adjustable. Right handle door available.

The Bastion UL-TL-30 features: the latest developments in a series of high quality safes. Fire and theft resistant, the safe has advanced design features to protect against conventional tools, hammers, chisels, wedges, drills and explosive attacks. This safe will protect your valuables like no other safe in its class.

Options include right handle door, private interior compartment with key or combination lock, additional shelves and a 144 hour time clock.



ULTL-30	INTERNAL			EX	TERI	NAL	CUBIC	QUANTITY	WEIGHT ,	HT , DOOR SWING		
MODEL	Н	W	D	Н	W	D	CAPACITY	SHELVES	(lbs.)	Α	В	
2217	22	17	16	29	24	27	3.47	1	1268	49.00	44.00	*
2618	26	18	18	33	25	29	4.87	ब्र	1497	50.50	44.75	
3320	33	20	18	40	27	29	6.88	2	1914	54.50	49.50	
4520	45	20	18	52	27	29	9.37	3	2396	54.50	49.25	
5220	52	20	24	59	27	35	14.44	3	3018	56.50	49.25	
6422	64	22	24	71	29	35	19.56	4	3734	62.00	53.00	
6434	64	34	20	71	41	31	25.18	4	4420	69.00	77.00	
7036	70	36	26	77	43	37	37.91	. 5	5427	77.00	81.25	
ADD ADDITIONAL 2in. FOR HANDLE & HINGES												